

OREGON STATE UNIVERSITY REQUEST FOR QUOTE (RFQ)

REQ JK188763Q REQ DE DATE: May 17, 2017 by 10:00 am PT							ISSUE DATE:		Ma	ıy 12, 20)17	
DEPARTMENT: College of Engineering, MIME	RFQ#			JK188763Q			-			y 17, 20		
ADDRESS: 204 Rogers Hall E-MAIL: jennifer.koehne@oregonstate.edu CITY, STATE ZIP: Corvallis OR 97331 REQUIRED DELIVERY DATE: June 15, 2017 FAX: 541-737-2170 TTEM DESCRIPTION QTY UNIT UNIT PRICE TOTAL PRICE 1 *Laser Tracker/Optical Coordinate Measuring Machine (CMM) 1 each Minimum Specifications a. Measure Absolute Cartesian (XYZ) position of a target position from 2-5[m] distance. b. Angular acceleration of 10 [rad/sec²] or higher. c. Provide measurement accuracy of +/-15[micron] + 8[micron/meter] d. Provide dynamic locking to the target with +/-12 [micron] accuracy. c. Displacement measurement resolution of 0.5 [micron] f. Continuously (dynamically) take measurement data at 1000 [points/sec] sampling. g. Software system for user interface and data analysis. h. Rotation envelope of 380[deg] horizontal and 100[deg] vertical. i. System including necessary components to conduct single target measurement. j. Warranty and technical support. Desired Specifications a. Advanced software system for robot calibration. b. Probes for orientation measurement. *System to be used in dynamic measurement. *System to be used in dynamic measurement. Desired Specifications a. Advanced software system for robot calibration. b. Probes for orientation measurement. *System to be used in dynamic measurement of industrial robot endeffector motion for calibration and accuracy improvement. Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed.			DELIVER TO:									
City, STATE ZIP: Corvallis OR 97331 TELEPHONE: 541-737-7353	DEPARTMENT:			College of Engineering, MIME			NAME:	Jennifer Koehne				
City, STATE ZIP: Corvallis OR 97331 TELEPHONE: 541-737-7353	ADDR	ESS:	2				E-MAIL:		jennifer.koehne@oregonstate.edu			
TEM DESCRIPTION QTY UNIT UNIT PRICE TOTAL PRICE							TELEPHONE:		541-737-7353			
#*Itaser Tracker/Optical Coordinate Measuring Machine (CMM) #*Itaser Tracker/Optical Coordinate Machine (CMM) #*Itaser Tracker/Optical Coordinate Machine (CMM) #*Itaser Tracker/Optical Coordinate Machine (CMM) #*Itaser Tracker (CMM) #*Itaser Tracker (CMM) #*Itaser Tracker (CMM) #*Itaser (CM	•						FAX:					
*Laser Tracker/Optical Coordinate Measuring Machine (CMM) Minimum Specifications a. Measure Absolute Cartesian (XYZ) position of a target position from 2~5[m] distance. b. Angular acceleration of 10 [rad/sec²] or higher. c. Provide measurement accuracy of +/-15[micron] + 8[micron/meter] d. Provide dynamic locking to the target with +/-12 [micron] accuracy. e. Displacement measurement resolution of 0.5 [micron] f. Continuously (dynamically) take measurement data at 1000 [points/sec] sampling. g. Software system for user interface and data analysis. h. Rotation envelope of 360[deg] horizontal and 100[deg] vertical. i. System including necessary components to conduct single target measurement. j. Warranty and technical support. Desired Specifications a. Advanced software system for robot calibration. b. Probes for orientation measurement. *System to be used in dynamic measurement of industrial robot endeffector motion for calibration and accuracy improvement. Discounts, if applicable, including educational Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed. TOTAL					, -			Q				
Minimum Specifications a. Measure Absolute Cartesian (XYZ) position of a target position from 2~5[m] distance. b. Angular acceleration of 10 [rad/sec²] or higher. c. Provide measurement accuracy of +/-15[micron] + 8[micron/meter] d. Provide dynamic locking to the target with +/-12 [micron] accuracy. e. Displacement measurement resolution of 0.5 [micron] f. Continuously (dynamically) take measurement data at 1000 [points/sec] sampling. g. Software system for user interface and data analysis. h. Rotation envelope of 360[deg] horizontal and 100[deg] vertical. i. System including necessary components to conduct single target measurement. j. Warranty and technical support. Desired Specifications a. Advanced software system for robot calibration. b. Probes for orientation measurement. *System to be used in dynamic measurement of industrial robot endeffector motion for calibration and accuracy improvement. 2 Discounts, if applicable, including educational Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed.							e (CMM)					
from 2~5[m] distance. b. Angular acceleration of 10 [rad/sec²] or higher. c. Provide measurement accuracy of +/-15[micron] + 8[micron/meter] d. Provide dynamic locking to the target with +/-12 [micron] accuracy. e. Displacement measurement resolution of 0.5 [micron] f. Continuously (dynamically) take measurement data at 1000 [points/sec] sampling. g. Software system for user interface and data analysis. h. Rotation envelope of 360[deg] horizontal and 100[deg] vertical. i. System including necessary components to conduct single target measurement. j. Warranty and technical support. Desired Specifications a. Advanced software system for robot calibration. b. Probes for orientation measurement. *System to be used in dynamic measurement of industrial robot endeffector motion for calibration and accuracy improvement. 2 Discounts, if applicable, including educational 1 each Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed.	•						<u> </u>	-				
b. Angular acceleration of 10 [rad/sec²] or higher. c. Provide measurement accuracy of +/-15[micron] + 8[micron/meter] d. Provide dynamic locking to the target with +/-12 [micron] accuracy. e. Displacement measurement resolution of 0.5 [micron] f. Continuously (dynamically) take measurement data at 1000 [points/sec] sampling. g. Software system for user interface and data analysis. h. Rotation envelope of 360[deg] horizontal and 100[deg] vertical. i. System including necessary components to conduct single target measurement. j. Warranty and technical support. Desired Specifications a. Advanced software system for robot calibration. b. Probes for orientation measurement. *System to be used in dynamic measurement of industrial robot endeffector motion for calibration and accuracy improvement. 2 Discounts, if applicable, including educational 1 each Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed.		a. Measure Absolute Cartesian (XYZ) position of a target position										
c. Provide measurement accuracy of */-15[micron] + 8[micron/meter] d. Provide dynamic locking to the target with */-12 [micron] accuracy. e. Displacement measurement resolution of 0.5 [micron] f. Continuously (dynamically) take measurement data at 1000 [points/sec] sampling. g. Software system for user interface and data analysis. h. Rotation envelope of 360[deg] horizontal and 100[deg] vertical. i. System including necessary components to conduct single target measurement. j. Warranty and technical support. Desired Specifications a. Advanced software system for robot calibration. b. Probes for orientation measurement. *System to be used in dynamic measurement of industrial robot endeffector motion for calibration and accuracy improvement. 2 Discounts, if applicable, including educational 1 each Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed.												
accuracy. c. Displacement measurement resolution of 0.5 [micron] f. Continuously (dynamically) take measurement data at 1000 [points/sec] sampling. g. Software system for user interface and data analysis. h. Rotation envelope of 360[deg] horizontal and 100[deg] vertical. i. System including necessary components to conduct single target measurement. j. Warranty and technical support. Desired Specifications a. Advanced software system for robot calibration. b. Probes for orientation measurement. *System to be used in dynamic measurement of industrial robot endeffector motion for calibration and accuracy improvement. 2 Discounts, if applicable, including educational 1 each Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed.		c. Provide measurement accuracy of +/-15[micron] +										
f. Continuously (dynamically) take measurement data at 1000 [points/sec] sampling. g. Software system for user interface and data analysis. h. Rotation envelope of 360[deg] horizontal and 100[deg] vertical. i. System including necessary components to conduct single target measurement. j. Warranty and technical support. Desired Specifications a. Advanced software system for robot calibration. b. Probes for orientation measurement. *System to be used in dynamic measurement of industrial robot endeffector motion for calibration and accuracy improvement. Discounts, if applicable, including educational 1 each Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed.		d. Provide dynamic locking to the target with +/-12 [micron]										
[points/sec] sampling. g. Software system for user interface and data analysis. h. Rotation envelope of 360[deg] horizontal and 100[deg] vertical. i. System including necessary components to conduct single target measurement. j. Warranty and technical support. Desired Specifications a. Advanced software system for robot calibration. b. Probes for orientation measurement. *System to be used in dynamic measurement of industrial robot endeffector motion for calibration and accuracy improvement. Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed. TOTAL		e. Displacement measurement resolution of 0.5 [micro				-						
h. Rotation envelope of 360[deg] horizontal and 100[deg] vertical. i. System including necessary components to conduct single target measurement. j. Warranty and technical support. Desired Specifications a. Advanced software system for robot calibration. b. Probes for orientation measurement. *System to be used in dynamic measurement of industrial robot endeffector motion for calibration and accuracy improvement. Discounts, if applicable, including educational 1 each Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed.							data at 1000					
i. System including necessary components to conduct single target measurement. j. Warranty and technical support. Desired Specifications a. Advanced software system for robot calibration. b. Probes for orientation measurement. *System to be used in dynamic measurement of industrial robot endeffector motion for calibration and accuracy improvement. Discounts, if applicable, including educational 1 each Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed.		g. Software system f			-							
measurement. j. Warranty and technical support. Desired Specifications a. Advanced software system for robot calibration. b. Probes for orientation measurement. *System to be used in dynamic measurement of industrial robot endeffector motion for calibration and accuracy improvement. Discounts, if applicable, including educational 1 each Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed.						٠.						
Desired Specifications a. Advanced software system for robot calibration. b. Probes for orientation measurement. *System to be used in dynamic measurement of industrial robot endeffector motion for calibration and accuracy improvement. Discounts, if applicable, including educational 1 each Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed.						uct single target						
a. Advanced software system for robot calibration. b. Probes for orientation measurement. *System to be used in dynamic measurement of industrial robot endeffector motion for calibration and accuracy improvement. 2 Discounts, if applicable, including educational 1 each Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed. TOTAL		j.	Warra	nty and tec	chnical support.							
effector motion for calibration and accuracy improvement. 2 Discounts, if applicable, including educational 1 each Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed. TOTAL		 Advanced software system for robot calibration. 										
Delivery is f.o.b. destination, prepaid and allowed. Shipping, freight and handling must be included in quoted prices. Additional costs for such are disallowed. TOTAL		*System to be used in dynamic measurement of industrial robot end- effector motion for calibration and accuracy improvement.										
must be included in quoted prices. Additional costs for such are disallowed. TOTAL	2	Discounts, if applicable, including educational						1		each		
must be included in quoted prices. Additional costs for such are disallowed. TOTAL												
										ling	TOTAL	
							Jaon are arean		PRICES VALID THROUGH:			

Please see page 2 for Special Instructions, Vendor Information and Signature- Page 2 must be returned with RFQ signed.



OREGON STATE UNIVERSITY REQUEST FOR QUOTE (RFQ)

SPECIAL INSTRUCTIONS:	VENDOR INFORMATION:								
	COMPANY:								
1. Unless otherwise specified, all items quoted are to be new, unused and not remanufactured in any									
way.									
2. Brand names are for the purpose of describing									
and establishing the characteristics desired and are not intended to limit or restrict competition. Quoters	ADDRESS:								
may submit quotes for substantially equivalent products unless the RFQ provides that a specific	CITY, STATE, ZIP:								
brand is necessary because of compatibility requirements, etc. All such brand substitutions shall	CONTACT NAME:								
be subject to approval by OSU. 3. Quoters must clearly identify all products quoted.	E-MAIL:								
Brand name and model or number must be shown. 4. Only documents issued as addenda by OSU	TELEPHONE:								
serve to change the RFQ in any way. 5. OSU reserves the right to make the award by	FAX:								
item, partial or whole lots, groups of items or entire	VENDOR SIGNATURE:								
quote, whichever is in the best interest of OSU. 6. OSU may reject any Quote not in compliance with	By signature below the undersigned certifies that they are authorized to act on behalf of the quoter and will comply with all aspects of the quote herein.								
the RFQ, attachments, and addenda, or if it is in the best interest of OSU.	SIGNATURE:								
This RFQ form must be completed, signed and returned with all required documents.	NAME/TITLE:								
This procurement is subject to the indicated Oregon State University Standard Terms and Conditions for: ⊠ Goods									
☐ Services ☐ Purchase Order Construct	ction 🗌 Software. 🗈	The indicated terms and conditions may be viewed at							
http://pacs.oregonstate.edu/terms-and-cond	litions	nttp://pacs.oregonstate.edu/terms-and-conditions							