

[illegible]

MARK	DESCRIPTION		
ACT-1	-	GWB-3	-
		GWB-4	-
CONC-1	-		
CONC-2	-	P-1	-
CONC-E	-	P-2	-
CONC-N	-	P-3	-
		P-4	-
CPT-1	-	P-5	-
CPT-2	-	P-6	-
CT-1	-	RB-1	-
CT-2	-	RB-2	-
CT-3	-		
		VCT-1	-
GWB-1	-	VCT-2	-
GWB-2	-		


ACT	ACOUSTICAL CEILING TILE	P	PAINT
ACT-E	ACOUSTICAL CEILING TILE - EXISTING	PLAM	PLASTIC LAMINATE
ALSF	ALUMINUM STOREFRONT	PLYWD	PLYWOOD
CONC	CONCRETE	PT	PORCELAIN TILE
CONC-G	CONCRETE - GRIND	RB	RUBBER BASE
CONC-E	CONCRETE - EXISTING	S	STAIN
CONC-N	CONCRETE - NEW	SM	SHEET METAL
CM	CONCRETE MASONRY	SLR	SEALER
CPT	CARPET	SV	SHEET VINYL
CT	CERAMIC TILE	SVB	SHEET VINYL SELF BASE
E	EXISTING	TB	TILE BASE
FRP	FACTORY FINISH	VCT	VINYL COMPOSITION TILE
FRP	FIBERGLAS REINFORCED PLASTIC PANEL	WD	WOOD
GALV	GALVANIZED		
GSM	GALVANIZED SHEET METAL		
GWB	GYPSUM WALL BOARD		
MTL	METAL		

[illegible][illegible]

1. CONTRACTOR SHALL FIELD VERIFY ALL
ROUGH OPENINGS PRIOR TO FABRICATION OF
ALL DOOR, WINDOW, & RELITE FRAMES

AL	ALUMINUM
CRT	CURTAIN
CSF	CLEAR SATIN FINISH
EX	EXISTING
E	EXISTING
FF	FACTORY FINISH
FRRG	FIRE RESISTANCE RATED
HM	HOLLOW METAL
IA	INTERIOR ALUMINUM
IG	INSULATED GLASS
ITG	INSULATED TEMPERED GLASS
NR	NON RATED
P	PAINT
PL	PLASTIC LAMINATE
RG	RATED GLAZING
S	STAIN
SLR	SEALER
STL	STEEL
STL I	INSULATED STEEL
TG	TEMPERED GLASS
V	VINYL
WD	WOOD
60M	60 MINUTE FIRE RATED

1. ALL METAL DOORS AND METAL FRAMES TO BE PRIMED AND PAINTED
2. ALL STAIN GRADE WOOD DOORS, FLUSH OR RAISED PANEL, ARE TO BE PREPPED AND STAINED. ALL DOOR CASINGS, WHETHER WOOD OR WOOD CLAD METAL ARE TO BE STAINED AND SEALED.
3. MITER TRIM AT ALL CORNERS - TYPICAL ALL DOORS, UNO.
4. ALL GLAZING IN DOORS SHALL BE SAFETY GLASS.
5. STOREFRONT GLAZING AND HOLLOW METAL RELITE DIMENSIONS SHOWN TO WINDOW UNIT SIZE. SEE DETAILS FOR ADDITIONAL INFORMATION ON STUD OPENINGS.
6. ALL ALUMINUM STOREFRONT GLAZING TO BE CLEAR FIXED GLASS UNO.
7. ALL HOLLOW METAL RELITE GLAZING TO BE CLEAR FIXED GLASS UNO.
8. PROVIDE SAFETY GLASS IN LOCATIONS AS REQUIRED BY CODE.


$$1/4'' = 1'-0''$$