

### CEILING PLAN NOTES

- 1 GYP BD SOFFIT @ +7'-0"
- 2 CUT EXIST SUSPENDED CLG SYSTEM @ NEW DOOR TRACK. MOUNT TO DOOR TRACK W/ NEW GRID RAIL TO MATCH EXIST SYSTEM. REPLACE DAMAGED TRACK AND PANELS AS REQUIRED - MATCH (E).
- 3 CUT EXIST SUSPENDED CLG SYSTEM @ NEW GYP BD SOFFIT. PROVIDE NEW EDGE RAIL TO MATCH EXIST SYSTEM. REPLACE DAMAGED TRACK AND PANELS AS REQUIRED - MATCH (E).
- 4 NEW CLG. 4" STL. JSTS @ 16" OC W/ 3/8" X GYP BD OVER 1/2" PLYWD SHEATHING.
- 5 24"X12" VENTILATION GRILLE IN NEW CLG. INST'LL W/ FASTENERS INSIDE OF IT CLOSET ONLY.
- 6 PROVIDE NEW SPRINKLER HEAD WITHIN SAFE CLOSET AND TIE INTO EXIST SPRINKLER SYSTEM. CONNECTION TO PROVIDE DRAWINGS AS REQUIRED BY THE CITY OF ASHLAND.
- 7 NEW BULK HEAD WALL FROM SHELF TO SOFFIT ABOVE.
- 8 PROVIDE ACCESS HOLE THROUGH CLG FOR CABLING.
- 9 CUT GRID AS REQUIRED FOR (M) SOFFITS AND BULKHEADS. RE-USE TRACK AND CEILING PANELS WHERE POSSIBLE. REPLACE DAMAGED TRACK AND PANELS AS REQUIRED - MATCH (E).
- 10 LINE OR EXIST GYP BD SOFFIT.
- 11 NEW WIRELESS ACCESS POINT IN CEILING TILE.

### EQUIPMENT LIST


- ALL EQUIPMENT ON THIS LIST IS TENANT PROVIDED. TENANT INSTALLED.
- 1 PERSONAL TELLER MACHINE
  - 2 EQUIPMENT RACKS
  - 3 CHECK SCANNER
  - 4 RECEIPT PRINTER
  - 5 CARD SCANNER
  - 6 PHONE
  - 7 SIGNATURE PAD
  - 8 PIN PAD
  - 9 CEILING MOUNTED WIRELESS ACCESS POINT
  - 10 MULTIFUNCTION PRINTER
  - 11 WALL MOUNTED MONITOR
  - 12 CARD PRINTER
  - 13 CHECK PRINTER
  - 14 DOCUMENT SHREDDER
  - 15 SAFE

### GENERAL CEILING NOTES

1. SUSPENDED CEILING TO BE SEISMICALLY RESTRAINED PER DETAIL Z/M3.1.
2. SEE M3.1 & E3.1 FOR ADDITIONAL INFORMATION.

### LEGEND

- EXISTING TO REMAIN.
- - - EXISTING TO BE REMOVED.
- ▭ AREA OF (E) SUSPENDED CEILING TO BE MODIFIED AND/OR REPLACED/REPAIRED AS REQUIRED.




- NOTES:
- A. ALL HANGERS AND SUPPORTS TO BE ATTACHED W/ (4) TURNS IN 3/4" TYP.
  - B. SUPPORT EACH LIGHT FIXTURE INDEPENDENTLY OF CEILING TILE W/ (1) #12 WIRE @ TWO CORNERS DIAGONALLY ACROSS FROM ONE ANOTHER.

#### MINIMUM REQUIREMENTS:

1. MINIMUM INTERSECTION STRENGTH LIMITS @ MT / CT = 180 LBS.
2. VERTICAL HANGER WIRE 12-GAUGE @ 4'-0" O.C.
3. CONNECTION DEVICE FROM VERTICAL WIRE TO THE STRUCTURE ABOVE MUST SUSTAIN MIN. 100 LBS
4. MAIN TEE CLASSIFICATION = HEAVY DUTY.
5. 1/8" MAX. PLUMB OF VERTICAL HANGER WIRES.
7. GRID END / WALL CLEARANCE = MIN. 3/4"
8. PERIMETER CLOSURE (MOLDING) WIDTH = MIN. 2"
9. GRID CONNECTION TO PERIMETER ATTACHED ON TWO ADJACENT WALLS.
10. PERIMETER TEE ENDS TIED TOGETHER.
11. HORIZONTAL RESTRAINT (SPLAY WIRES OR RIGID BRACING) WITHIN 2" OD INTERSECTION AND SPLAYED 90° APART AT 45° ANGLES.
12. COMPRESSION POSTS (STRUTS) 1/2" O.C. IN BOTH DIRECTIONS, STARTING 6" FROM WALLS.
13. SPLAY BRACING CONNECTION STRENGTH 200 LBS OR THE DESIGN LOAD, WHICHEVER IS GRATER.
14. PARTITION ATTACHMENT MUST BE INDEPENDENT OF CEILING SPLAY BRACING.
15. SEISMIC SEPARATION JOINT IS REQUIRED FOR AREAS > 2,500 S.F. (OR FULL HEIGHT PARTITION).
16. RIGID BRACING FOR CEILING PLANE ELEVATION CHANGES.

### CEILING RESTRAINT DETAIL 2

1/4"=1'-0"



### REFLECTED CEILING PLAN

1/2" = 1'-0"

1


**Kistler+  
Small  
+White**  
architects

66 WATER STREET  
SUITE 101  
ASHLAND, OR  
TEL: 941.488.8200

PERMIT/BID SET

6-2-2015

FOR CONSTRUCTION



**ROGUE CREDIT UNION @ SOU  
TENANT IMPROVEMENT - STEVENSON UNION**  
OWNER: Rogue Credit Union  
PROJECT ADDRESS: 1250 Siskiyou Boulevard

REVISIONS

REFLECTED  
CEILING PLAN

PROJECT: 15-017  
ISSUE DATE: 06-02-15  
SHEET:

**A5.1**